

WHAT IS CLAIMED IS:

1. A packet service method for a base station controller (BSC) in a mobile communication system, comprising the steps of:
 - 5 receiving a packet to be transmitted for a mobile station (MS);
 - adding a field containing time information necessary for packet transmission on a radio link to the received packet; and
 - transmitting the packet including the field to a base station transceiver sub-system (BTS).
- 10 2. The packet service method of claim 1, further comprising the steps of:
 - determining whether a sequence number is to be used for the packet transmission; and
 - 15 adding a field containing the sequence number of the packet to the packet if it is determined that the sequence number is to be used.
3. The packet service method of claim 1, wherein the time information is an action time when the packet is to be transmitted on the radio
 - 20 link.
4. The packet service method of claim 1, wherein the time information includes an action time when the packet is to be transmitted on the radio link and a waiting time for which the packet waits to be transmitted until
 - 25 there is an available radio link.
5. A packet service method for a base station transceiver sub-system (BTS) in a mobile communication system, comprising the steps of:
 - storing a packet received from a base station controller (BSC);
 - 30 determining whether a current time is an action time when the received

packet is to be transmitted based on time information set in a predetermined field of the packet; and

transmitting the packet to a mobile station (MS) on a radio link if the current time is an action time.

5

6. The packet service method of claim 5, wherein the action time is a time set in the predetermined field of the packet. .

7. The packet service method of claim 5, wherein the action time is
10 sum of a time set in the predetermined field of the packet and a pre-negotiated time.

8. A packet service method for a base station transceiver sub-
system (BTS) in a mobile communication system, comprising the steps of:
15 storing a packet received from a base station controller (BSC);
determining whether there is a available radio link;
transmitting the packet to a mobile station (MS) on a radio link if there is
a available radio link;
determining whether a waiting time set in a predetermined field of the
20 packet has expired if there is no available radio link; and
discarding the packet if the waiting time has expired and determining
whether there is an available radio link if the waiting time has not expired.

9. A packet service method for a base station transceiver sub-
25 system (BTS) in a mobile communication system, comprising the steps of:
storing a packet received from a base station controller (BSC);
determining whether a waiting time set in a predetermined field of the
packet has expired;
discarding the packet if the waiting time has expired and determining
30 whether there is an available radio link if the waiting time has not expired;

determining whether the waiting time has expired if there is no available radio link and determining whether the current time is an action time based on the time information if there is an available radio link; and

transmitting the packet to a mobile station (MS) on the radio link at the
 5 action time and determining whether the waiting time has expired if the current time is not the action time.

10. The packet service method of claim 9, wherein the action time is sum of a time set in the predetermined field of the packet.

10

11. The packet service method of claim 9, wherein the action time is sum of a time set in the predetermined field of the packet and a pre-negotiated time.

15

12. A packet service method for a base station controller (BSC) in a mobile communication system, comprising the steps of:

receiving a packet to be transmitted for a mobile station (MS);

determining whether a sequence number is to be used for the packet;

adding a field containing the sequence number of the packet to the packet

20 if it is determined that the sequence number is to be used; and

transmitting the packet including the field to a base station transceiver sub-system (BTS).

13. A packet service method for a base station transceiver sub-
 25 system (BTS) in a mobile communication system, comprising the steps of:

storing a packet received from a mobile station (MS);

determining whether a sequence number is to be used for the packet;

adding a field containing the sequence number of the packet to the packet if it is determined that the sequence number is to be used; and

30 transmitting the packet including the field to a base station controller

(BSC).

14. A packet service method for a base station controller (BSC) in a mobile communication system, comprising the steps of:

storing a packet received from a base station transceiver sub-system

5 (BTS);

determining whether a current time is an action time based on a predetermined period;

checking whether the stored packet has an error at the action time; and

transmitting the packet to a higher layer system if the packet has no

10 errors.

15. A packet service method for a base station controller (BSC) in a mobile communication system, comprising the steps of:

storing a packet received from a base station transceiver sub-system

15 (BTS);

determining whether a sequence of the packet is valid or not by checking a sequence number set in the packet; and

transmitting the packet to a high layer system if the packet sequence is valid and discarding the packet if the packet sequence is invalid.

20

16. A packet service method in a mobile communication system, comprising the steps of:

adding a field containing time information necessary for packet transmission on a radio link to a packet to be transmitted for a mobile station (MS) in a base station controller (BSC) and transmitting the packet including the field from the BSC to a base station transceiver sub-system (BTS);

storing the packet received from the BSC in the BTS;

determining whether a current time is an action time based on the time information set in the field of the packet in the BTS; and

30 transmitting the packet from the BTS to the MS on a radio link at the

action time.

17. The packet service method of claim 14, wherein the action time is a time set in the field.

5

18. The packet service method of claim 14, wherein the action time is the sum of a time set in the field and a pre-negotiated time.

19. The packet service method of claim 14, further comprising the
10 step of adding a field containing a sequence number of the packet to the packet in the BSC.

20. The packet service method of claim 14, wherein the time
information includes a waiting time for which the packet waits to be transmitted
15 until there is an available radio link, further comprising the step of discarding the packet if the packet is not transmitted until the waiting time expires.

21. A packet service method in a mobile communication system,
comprising the steps of:
20 storing a packet received from a mobile station (MS) in a base station transceiver sub-system (BTS), adding a field containing a sequence number of the packet to the packet in the BTS, and transmitting the packet including the field from the BTS to a base station controller (BSC);

determining whether a sequence of the packet is valid or not by checking
25 the sequence number set in the header of the packet in the BSC; and

transmitting the packet from the BSC to a high layer system if the packet sequence is valid and discarding the packet if the packet sequence is invalid.